

TECHNICAL DATA SHEET

ANY WAY 15W-40

Premium Quality Diesel and Gasoline Engine Oil

DESCRIPTION

Multi-grade engine oils developed to meet the current lubrication demands of the latest diesel and gasoline engines. Formulated by carefully selected base oils combined with superior additive technology. Keeps engines clean while reducing wear.

APPLICATION & USE

It is applied to both turbo charged and naturally aspirated engines with or without catalytic converters. Intended for the use in mixed fleet of passenger cars, taxis and light commercial vehicles. It can be used in gasoline, diesel and gas engines. Durable in critical work environments and temperature conditions.

KEY BENEFITS

Oxidation Resistance
Good Wear Protection
Low Evaporation
Keeps Engine Clean

SPECIFICATION

API: SL/CF, ACEA: E2/A3/B3, MB: 229.1, VW: 505.00/502.00

CHARACTERISTICS	METHOD	UNIT	RESULTS
			15W-40
Density 15°	ASTM D-1298	KG/L	0,880
Viscosity at 40°	ASTM D-445	cSt	116
Viscosity at 100°	ASTM D-445	cSt	15
Viscosity Index	ASTM D-2270	-	134
Pour Point	ASTM D-97	°C	-25
Flash Point C.O.C	ASTM D-92	°C	230
TBN	ASTM D-2896	Mg KOH/g	11.5