

## TECHNICAL DATA SHEET

# ATF DEXRON III H

### High Quality Synthetic Automatic Transmission Fluid

#### DESCRIPTION

High quality automatic transmission fluids, designed to resist oxidation and to provide smooth operation of many automotive transmission systems. This high quality fluid has excellent wear protection which prolongs the life of the transmission system. Synthetic base oils together with special additive package ensure the trouble free operation.

#### APPLICATION & USE

Intended for use in passenger car automatic transmissions, heavy duty automatic transmissions, and power steering units.

#### KEY BENEFITS

Oxidation Resistance.  
Excellent Wear Protection.  
Smooth Operation

#### SPECIFICATION

Dexron III-H/G/F, FORD Mercon, Allison C-4, MB 236.1, CAT TO-2, ZF TE-ML-14A-17C

CHARACTERISTICS	METHOD	UNIT	RESULTS
			Dexron III H
Density 15°	ASTM D-1298	KG/L	0,860
Viscosity at 40°	ASTM D-445	cSt	37
Viscosity at 100°	ASTM D-445	cSt	7.3
Viscosity Index	ASTM D-2270	-	166
Pour Point	ASTM D-97	°C	-30
Flash Point C.O.C	ASTM D-92	°C	200
TBN	ASTM D-2896	Mg KOH/g	-