

TECHNICAL DATA SHEET

MULTI SYNTHETIC 75W-90

Ultra High Performance Synthetic Gear Oil

DESCRIPTION

Multi-grade synthetic gear oils, specifically designed to lubricate manual gearboxes in passenger vehicles and industrial applications. It is formulated by using high quality synthetic base oils together with an advanced additive technology, which delivers good anti-wear and anti-rust abilities.

APPLICATION & USE

Intended for use in manual transmissions and rear axles of commercial and off-highway construction vehicles operating in severe conditions and where mineral oil cannot be used. Recommended for vehicles, equipment and machines where an API: GL 5 performance level is required.

KEY BENEFITS

Outstanding Oxidation Stability
Excellent Wear Protection
Excellent Corrosion Protection

SPECIFICATION

API: GL-5, MIL-L-2105 D, MT-1, MAN 342, ZF TE-ML-02A-05A-07A-12A

CHARACTERISTICS	METHOD	UNIT	RESULTS
			75W-90
Density 15°	ASTM D-1298	KG/L	0,870
Viscosity at 40°	ASTM D-445	cSt	105
Viscosity at 100°	ASTM D-445	cSt	14.5
Viscosity Index	ASTM D-2270	-	142
Pour Point	ASTM D-97	°C	-40
Flash Point C.O.C	ASTM D-92	°C	210
TBN	ASTM D-2896	Mg KOH/g	-