



TECHNICAL DATA SHEET

MULTI VALVO 85W-140

High Performance Multi-grade Gear Oil

DESCRIPTION

Multi-grade gear oils, specifically designed to lubricate manual gearboxes in passenger vehicles and industrial applications. It is formulated by using high quality base oils together with an advanced additive technology, which delivers good anti-wear and anti-rust abilities.

APPLICATION & USE

Intended for use in manual transmissions and rear axles of passenger, commercial and off-highway construction vehicles operating in normal and severe conditions. Recommended for vehicles, equipment and machines where an API: GL 5 performance level is required.

KEY BENEFITS

Outstanding Oxidation Stability. Excellent Wear Protection. Excellent Corrosion Protection.

SPECIFICATION

API: GL-4/5, MT-1, SAE J2360

CHARACTERISTICS	METHOD	UNIT	RESULTS
			85W-140
Density 15°	ASTM D-1298	KG/L	0,905
Viscosity at 40°	ASTM D-445	cSt	340
Viscosity at 100°	ASTM D-445	cSt	25
Viscosity Index	ASTM D-2270	-	95
Pour Point	ASTM D-97	°C	-15
Flash Point C.O.C	ASTM D-92	°C	220
TBN	ASTM D-2896	Mg KOH/g	-